

MASK



PRISMATECH

COMPACT FLUORESCENT

1-26W
1-32W
1-42W

APPLICATION

Mask is suitable for indoor wall mounting.

HOUSING AND FACEPLATE

Precision die cast, copper free, aluminum. Conforms to ASTM A413.2.

DIFFUSER

Pressed soda lime glass diffuser, internally & externally ice etched, .21" thick. The interior surface of the glass is ribbed to provide maximum light diffusion; the diffuser is encased in the faceplate.

REFLECTOR

Die formed painted aluminum, high reflectance white.

ELECTRICAL

Electronic HPF compact fluorescent ballast for 120 through 277 volts, 50/60 Hz. Minimum starting temperature 0° F (-18° C), THD less than 5%. For 347V operation consult factory.

LAMPS

Compact fluorescent quad or triple tube lamps, 26W G24q-3 base, 32W GX24q-3 base, or 42W GX24q-4 base. Lamps supplied by others.

FINISH

The standard finish includes a 10-step process of cleaning, pre-treatment and painting. Electrostatically applied and thermally cured (TGIC) polyester powder coat paint is applied to each fixture. This high quality process ensures the finish will last for years without fading, chipping or cracking. The paint finish and process conforms to ASTM B117-90 and UNI-ISO 9227 (Salt Spray) and ISO2409. For special finishes, consult factory.

LISTINGS

UL and cUL Listed. Suitable for damp locations.



1-26W
1-32W
1-42W


GROSS WEIGHT 8.9 LBS
NET WEIGHT 6.35 LBS

PRODUCT CODE _____

PROJECT _____

TYPE _____

LUMINAIRE	LAMP	VOLTAGE	FINISH
072013	1-26 W G24q-3	120/277	White
072017	1-26 W G24q-3	120/277	Metallic Anthracite
072015	1-26 W G24q-3	120/277	Metallic Gray
072025	1-32 W GX24q-3	120/277	White
072029	1-32 W GX24q-3	120/277	Metallic Anthracite
072027	1-32 W GX24q-3	120/277	Metallic Gray
072026	1-42 W GX24q-4	120/277	White
072030	1-42 W GX24q-4	120/277	Metallic Anthracite
072028	1-42 W GX24q-4	120/277	Metallic Gray



Prisma North America, Inc.
300 Petty Road, Suite C - Lawrenceville, GA 30043
Voice 770.822.2115 - Fax 770.822.9925
Email: info@prismalighting.com



MASK




PRISMATECH


COMPACT FLUORESCENT

1-26W
1-32W
1-42W

1-26W



1-32W



1-42W

